

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 December 2005 (15.12.2005)

PCT

(10) International Publication Number  
**WO 2005/117729 A2**

(51) International Patent Classification<sup>7</sup>: **A61B 17/70**

[US/US]; 3030 Children's Way, Suite 410, San Diego, CA 92123 (US).

(21) International Application Number:  
PCT/US2005/014384

(74) Agents: **GEARY, William, C., III** et al.; Nutter McClen-  
nen & Fish LLP, World Trade Center West, 155 Seaport  
Boulevard, Boston, MA 02210-2604 (US).

(22) International Filing Date: 27 April 2005 (27.04.2005)

(25) Filing Language: English

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,  
MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM,  
PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY,  
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU,  
ZA, ZM, ZW.

(26) Publication Language: English

(30) Priority Data:  
10/709,795 28 May 2004 (28.05.2004) US

(71) Applicant (*for all designated States except US*): **DEPUY  
SPINE, INC.** [US/US]; 325 Paramount Drive, Raynham,  
MA 02767 (US).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **SLIVKA, Michael,  
A.** [US/US]; 90 Lehner Drive, Taunton, MA 02780  
(US). **SERHAN, Hassan, A.** [US/US]; 27 Forest Edge  
Road, South Easton, MA 02375 (US). **NEWTON, Peter**

(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: ANCHORING SYSTEMS AND METHODS FOR CORRECTING SPINAL DEFORMITIES



(57) Abstract: Spinal anchoring methods and devices are provided that are effective to correct spinal deformities while allowing some flexibility to the spinal. In particular, the methods and devices allow a spinal fixation element to mate to several adjacent vertebrae to maintain the vertebrae at a fixed distance relative to one another, yet to allow the orientation of each vertebrae relative to the fixation element to adjust as the orientation of the patient's spine changes.

WO 2005/117729 A2



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *without international search report and to be republished upon receipt of that report*

- 1 -

## ANCHORING SYSTEMS AND METHODS FOR CORRECTING SPINAL DEFORMITIES

### 5 FIELD OF THE INVENTION

The present invention relates to non-fusion methods and devices for correcting spinal deformities.

### BACKGROUND OF THE INVENTION

10 Spinal deformities, which include rotation, angulation, and/or curvature of the spine, can result from various disorders, including, for example, scoliosis (abnormal curvature in the coronal plane of the spine), kyphosis (backward curvature of the spine), and spondylolisthesis (forward displacement of a lumbar vertebra). Early techniques for correcting such deformities utilized external devices that apply force to the spine in an  
15 attempt to reposition the vertebrae. These devices, however, resulted in severe restriction and in some cases immobility of the patient. Thus, to avoid this need, several rod-based techniques were developed to span across multiple vertebrae and force the vertebrae into a desired orientation.

In rod-based techniques, one or more rods are attached to the vertebrae at several  
20 fixation sites to progressively correct the spinal deformity. The rods are typically pre-curved to a desired adjusted spinal curvature. Wires can also be used to pull individual vertebra toward the rod. Once the spine has been substantially corrected, the procedure typically requires fusion of the instrumented spinal segments.

While several different rod-based systems have been developed, they tend to be  
25 cumbersome, requiring complicated surgical procedures with long operating times to achieve correction. Further, intraoperative adjustment of rod-based systems can be difficult and may result in loss of mechanical properties due to multiple bending operations. Lastly, the rigidity and permanence of rigid rod-based systems does not allow growth of the spine and generally requires fusion of many spine levels, drastically  
30 reducing the flexibility of the spine.

Accordingly, there remains a need for improved methods and devices for correcting spinal deformities.

- 2 -

## SUMMARY OF THE INVENTION

The present invention provides various embodiments of spinal anchoring methods and devices for correcting spinal deformities. In one exemplary embodiment, a spinal anchoring device is provided having a bone-engaging member that is adapted to engage bone, and a receiver member that is movably coupled to the bone-engaging member and that is adapted to seat a spinal fixation element. The anchoring device can also include a fastening element, such as a set screw, that is adapted to mate to the receiver member to lock a fixation element in a fixed position relative to the receiver member while allowing the receiver member to move freely relative to the bone-engaging member.

The receiver member can have a variety of configurations, but in one exemplary embodiment the receiver member includes a recess formed in a proximal portion thereof that is adapted to seat a spinal fixation element. The recess is preferably spaced apart and separate from the cavity in the distal portion of the receiver member. The receiver member can also include a distal portion that is movably mated to the bone-engaging member, and a proximal portion having a recess formed therein for seating a spinal fixation element.

Movement of the receiver member relative to the bone-engaging member can vary, and in one embodiment the bone-engaging member can be pivotally coupled to the receiver member such that the receiver member pivots along an axis relative to the bone-engaging member. By way of non-limiting example, a pin member can extend through a distal end of the receiver member and through a proximal end of the bone-engaging member for pivotally mating the receiver member and the bone-engaging member. In another embodiment, the bone-engaging member can be polyaxially coupled to the receiver member. By way of non-limiting example, the bone-engaging member can include a spherical head formed on a proximal end thereof, and the receiver member can include a cavity formed in a distal portion thereof that is adapted to polyaxially seat the spherical head of the bone-engaging member. In other aspects, portions of the receiver member and/or the bone-engaging member can optionally include a surface coating, such as titanium oxide, nitride, or a cobalt-chrome alloy, that is adapted to facilitate movement of the receiver member relative to the bone-engaging member.

- 3 -

In another embodiment of the present invention, a spinal anchoring system is provided having a spinal fixation element, a spinal anchoring device having a bone-engaging member and a receiver member freely movably coupled to the bone-engaging member and configured to receive the spinal fixation element, and a fastening element that is receivable within the receiver member of the spinal anchoring device and that is configured to lock the spinal fixation element to the spinal anchoring device. The spinal fixation element can have a variety of configurations, and suitable spinal fixation elements include, for example, cables, tethers, rigid spinal rods, or flexible spinal rods. The spinal fixation can also be formed from a variety of materials include, for example, stainless steel, titanium, non-absorbable polymers, absorbable polymers, and combinations thereof.

In other embodiments the present invention provides a method for correcting spinal deformities that includes the step of implanting a plurality of anchoring devices into adjacent vertebrae in a spinal column. Each anchoring device preferably includes a bone-engaging member that is fixedly attached to the vertebra and a receiver member that is freely movable relative to the bone-engaging member and the vertebra. A spinal fixation element is then coupled to the receiver member on each anchoring device such that the fixation element extends between each of the adjacent vertebrae. Once properly positioned, the spinal fixation element is locked to the receiver member on each anchoring device to maintain the adjacent vertebrae at a fixed distance relative to one another while allowing free movement of each vertebrae in the fixed position.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1A is a side view of one embodiment of a spinal anchoring device in accordance with the present invention;

FIG. 1B is another side view of the spinal anchoring device shown in FIG. 1A;

FIG. 1C is a cross-sectional view of the spinal anchoring device shown in FIG. 1A taken across line A-A;

- 4 -

FIG. 1D is an enlarged view of a proximal portion of the spinal anchoring device shown in FIG. 1C;

5           FIG. 1E is an enlarged view of a proximal portion of another embodiment of a spinal anchoring device;

FIG. 2 is a side, partially cross-sectional view illustration of two spinal anchoring devices, as shown in FIG. 1A, implanted in adjacent vertebrae in accordance with one  
10           embodiment of a method for correcting spinal deformities;

FIG. 3A is a side view illustration of two spinal anchoring devices having receiver members coupled to a spinal fixation rod and having bone-engaging members implanted in adjacent vertebrae in accordance with another embodiment of a method for  
15           correcting spinal deformities; and

FIG. 3B illustrates the spinal anchoring devices shown in FIG. 3A with the receiver members pivoted relative to the bone-engaging members to allow for movement of the vertebrae.

20

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention generally provides spinal anchoring methods and devices that are effective to correct spinal deformities while allowing some flexibility to the spine. In particular, the methods and devices allow a spinal fixation element to mate to  
25           several adjacent vertebrae to maintain the vertebrae at a fixed distance relative to one another, yet to allow the orientation of each vertebrae in that fixed position to adjust as the orientation of the patient's spine changes, e.g., due to movement and/or growth. While various techniques can be used to provide for such a configuration, an exemplary anchoring device in accordance with one embodiment of the present invention generally  
30           includes a bone-engaging member that is adapted to be implanted in a vertebra, and a receiver member that is movably coupled to the bone-engaging member and that is effective to mate to a spinal fixation element. In use, when several anchoring devices are implanted within adjacent vertebrae in a patient's spine and a spinal fixation element is fixedly mated to each anchoring device, the spinal fixation element is effective to  
35           maintain the adjacent vertebrae at a desired fixed distance relative to one another. Each

- 5 -

vertebra can, however, change orientations in that fixed position relative to the spinal fixation element because the bone-engaging member implanted therein is movably attached to the receiver member mated thereto and mated to the spinal fixation element.

5 As a result, the spinal anchoring devices allow movement of the patient's spine. Such a technique can be advantageous for shortening and/or halting growth of the patient's spine, however the methods and devices can be used in a variety of other spinal applications. By way of non-limiting example, the device can be used for posterior dynamization to function as a decompressive device for stenosis and/or an adjunct to an  
10 intervertebral disc to unload the facets of the vertebra.

FIGS. 1A-1D illustrate one exemplary embodiment of a spinal anchoring device 10 that includes a receiver member 12 that is polyaxially coupled to a bone-engaging member 14. While the bone-engaging member 14 can have a variety of configurations, in this embodiment the bone-engaging member 14 is in the form of a polyaxial screw  
15 having a threaded shank 14b and a substantially spherical head 14a. The proximal end of the head 14a, in the illustrated embodiment, may be truncated to form a flattened proximal surface 14c that facilitates polyaxial movement of the bone engaging member 14 relative to the receiver member 12, as will be discussed in more detail below. The head 14a can also include a driver-receiving element formed in the flattened proximal  
20 end 14c for mating with a driver device. The driver-receiving element can be, for example, a socket 14d (FIGS. 1C-1D) formed within the proximal end 14c of the head 14a for receiving a driver tool which can be used to thread the bone-engaging member 14 into bone. A person skilled in the art will appreciate that virtually any device that is effective to mate to bone can be used in place of bone-engaging member 14, including,  
25 for example, screws, hooks, bolts, plates, etc., as long as the bone-engaging member 14 is movably coupled to the receiver member 12.

The receiver member 12 can also have a variety of configurations, however, in the illustrated embodiment the receiver member 12 is generally U-shaped and includes a proximal portion 12a having opposed side walls or legs 13a, 13b that are substantially  
30 parallel to one another and that define a recess 16 therebetween for seating a spinal fixation element 18. The spinal fixation element 18 can have a variety of configurations, and, by way of non-limiting example, it can be rigid, semi-rigid, bendable, flexible, etc. Suitable spinal fixation elements for use with the present invention include, by way of

- 6 -

non-limiting example, rods, tethers, cables, plates, etc. The spinal fixation element 18 can also be formed from a variety of materials including, for example, stainless steel, titanium, non-absorbable polymers, absorbable polymers, and combinations thereof. In  
5 certain applications, it may be desirable to provide a fixation element that is flexible to allow for bending, yet that is rigid in tension such that the fixation element can not stretch or lengthen. This is particularly useful in applications where it is necessary to prevent growth of the spine while allowing normal flexibility.

Still referring to FIGS. 1A-1D, the receiver member 12 also includes a distal  
10 portion 12b that is adapted to movably couple to the bone-engaging member 14. In particular, the distal portion 12b may include a seat 19 that is preferably effective to receive the head 14a of the bone-engaging member 14 such that the bone-engaging member 14 is polyaxially movable relative to the receiver member 12. In the illustrated embodiment, the seat 19 is defined by at least a portion of the walls of a substantially  
15 spherical cavity 20 formed in the distal portion 12b. The seat 19 is preferably complementary in shape to the head 14a. For example, in the illustrated embodiment, the seat 19 and the head 14a are spherical in shape. One skilled in the art will appreciate, however, that the seat 19 and head 14a need not be spherical in shape or complementary in shape; the seat 19 and head 14a may have any shape(s) sufficient to  
20 allow polyaxial motion of the bone engaging member 14 relative to the receiver member 12. As discussed above, in certain embodiments the proximal end of the head 14a may be truncated to facilitate polyaxial motion. As shown in FIGS. 1C, for example, the gap 17 between the fixation element 18 and the flattened proximal surface 14c provides an increased range of polyaxial motion to the head 14a within the cavity 20.

In the illustrated embodiment, the cavity 20, and thus the seat 19, is spaced apart  
25 from the recess 16 in the proximal portion 12a of the receiver member 12 to inhibit contact between the head 14a and the spinal fixation element 18, thus allowing polyaxial movement of the spherical head 14a of the bone-engaging member 14 without interference from the spinal fixation element 18 disposed in the recess 16. The spacing  
30 between the recess 16 in the proximal portion 12a and the cavity 20 in the distal portion 12b can be achieved using a variety of techniques, but in the illustrated embodiment the legs 13a, 13b each include a protrusion or ridge 22a, 22b formed therein that separates the recess 16 and the cavity 20, as shown in FIGS. 1C-1D. The ridges 22a, 22b together



- 7 -

define an opening 22c having a diameter  $D_o$  that is less than both the diameter  $D_r$  of the spinal fixation element 18 and the diameter  $D_b$  of the spherical head 14a of the bone-engaging member 14 to prevent passage of the fixation element 18 and the head 14a therethrough, thus separating the two components.

Since the diameter  $D_o$  of the opening 22c is preferably smaller than the diameter  $D_b$  of the head 14a of the bone-engaging member 14, the device 10 can be adapted to allow the bone-engaging member 14 to be inserted through the proximal portion 12a of the receiver member 12 to seat the head 14a in the spherical cavity 20. This can be achieved, for example, by expanding or pulling apart the legs 13a, 13b to increase the diameter  $D_o$  of the opening 22c, thereby allowing the spherical head 14a to pass therethrough. The head 14a can then be seated within the cavity 22 and the legs 13a, 13b can return to their original state. The spinal fixation element 18 can then be seated in the recess 16 in the proximal portion 12a of the receiver member 12 and the ridges 22a, 22b will prevent the fixation element 18 from passing therethrough into the cavity 22. The legs 13a, 13b can thereafter be locked in a fixed position relative to one another using a locking mechanism that mates to the legs. Exemplary locking mechanisms will be described in more detail below.

In other embodiments (not shown), rather than having ridges 22a, 22b formed on the legs 13a, 13b of the receiver member 12, the receiver member 12 can include an insert that is adapted to be disposed therein after the spherical head 14a is positioned within the cavity 22 in the distal portion 12b to separate the spherical head 14a from the fixation element 18. The insert can have any shape and size, but it is preferably adapted to complete the substantially spherical cavity 20 in the distal portion 12b of the receiver member 12, and to seat a spinal fixation element 18 extending through the receiver member 12. The insert can also be configured to merely sit within the receiver member 12, or it can be adapted to mate to the receiver member 12, e.g., using threads, a snap-fit, or some other engagement technique known in the art, such that the insert is retained at a desired location in the receiver member 12. In use, the insert will allow the bone-engaging member 14 to rotate freely within the cavity 20 in the distal portion 12b of the receiver member 12 because the insert does not bear against the spherical head 14a of the bone-engaging member 12. The insert will also allow the spinal fixation element 18 to be locked within the receiver member 12 using techniques which will be discussed in

- 8 -

more detailed below. A person skilled in the art will appreciate that a variety of other techniques can be used to allow the bone-engaging member 14 to be assembled and disassembled from the receiver member 12. By way of non-limiting example, the proximal and distal portions 12a, 12b of the receiver member 12 can be separate components that are matable to one another, e.g., using threads or other mating techniques known in the art. Such a configuration allows the head 14a of the bone-engaging member 14 to be seated within the cavity 20 in the distal portion 12b prior to mating the proximal and distal portions 12a, 12b of the receiver member 12 to one another. Other techniques not shown or described herein can also be used as long as the bone-engaging member 14 and the receiver member 12 are at least partially freely movable relative to one another. For example, in certain embodiments, the head 14a of the bone engaging member 14 may be inserted through the distal end of the receiver member 12. In such embodiments, the opening 12c may not be necessary and thus, as shown in FIG. 1E by way of non-limiting example, the cavity 20" and the recess 16" may be completely separated within the receiver member 12".

As previously indicated, the device 10 can also include a fastening element that is effective to lock the spinal fixation element 18 to the receiver member 12, and more preferably that is effective to lock the spinal fixation element 18 within the recess 16 in the receiver member 12 such that the spinal fixation element 18 cannot move relative to the receiver 12. The fastening element can have a variety of configurations, and it can be adapted to mate to inner and/or outer portions of the legs 13a, 13b on the receiver member. FIGS. 1B-1D illustrate one embodiment of a fastening element that is in the form of a threaded set screw 24 that is adapted to mate with corresponding threads formed within the receiver member 12, i.e., on the legs 13a, 13b. A person skilled in the art will appreciate that a variety of fastening elements known in the art can be used with the various spinal anchoring devices of the present invention and that the illustrated set screw 24 is merely one exemplary embodiment of a fastening element.

FIG. 2 illustrates the spinal anchoring device 10 shown in FIGS. 1A-1D in use. In the illustrated embodiment, two spinal anchoring devices 10, 10' are implanted in adjacent vertebrae 50, 52, however any number of spinal anchoring devices can be used and the number will vary depending on the nature of the procedure being performed. The devices 10, 10' are implanted in the vertebrae 50, 52 by inserting the bone-engaging

- 9 -

member 14, 14' of each device 10, 10' through the receiver member 12, 12' and then  
threading the bone-engaging member 14, 14' into the vertebra. As previously  
mentioned, this can be achieved using a driver tool that is adapted to engage a driver-  
receiving element, such as socket 14d, 14d', in the spherical head 14a, 14a' on each  
bone-engaging member 14, 14'. Once the bone-engaging members 14, 14' are  
implanted in the adjacent vertebrae 50, 52, a spinal fixation element, such as spinal rod  
18, is positioned within the receiver member 12, 12' of each device 10, 10'. Since the  
devices 10, 10' are preferably used to correct a spinal deformity, the position of each  
vertebra will likely need to be adjusted to correct the deformity in order to seat the rod  
18 within each receiver member 12, 12'. Once properly positioned, the rod 18 can be  
locked to each receiver member 12, 12' preferably by inserting a locking mechanism,  
such as a set screw, into the head of each receiver member 12, 12', thereby maintaining  
the vertebrae 50, 52 at a fixed distance apart from one another. Since each bone-  
engaging member 14, 14' is polyaxially movable relative to each receiver member 12,  
12', each vertebrae 50, 52 is free to move in that fixed position relative to the receiver  
member 12, 12' coupled thereto, thus allowing for movement of the spine.

FIGS. 3A-3B illustrate yet another embodiment of a spinal anchoring device 100.  
While the drawings illustrate two devices 100, 100' implanted in adjacent vertebrae 150,  
152, the devices 100, 100' are substantially similar and those only one device 100 will be  
described. As shown, the device 100 is similar to device 10 in that it includes a receiver  
member 112 having a proximal portion 112a for seating a spinal fixation element 118,  
and a distal portion adapted to couple to a bone-engaging member 114. In this  
embodiment, however, rather than allowing polyaxial movement of the receiver member  
112 relative to the bone-engaging member 114, the receiver member 112 pivots along an  
axis, indicated by point A, relative to the bone-engaging member 114. Pivotal  
movement can be achieved using a variety of techniques, and in one exemplary  
embodiment a bearing element can be formed between the components 112, 114. The  
bearing element can be, for example, a pin member 120 that extends through the distal  
portion 112b of the receiver member 112 and through a portion of the bone-engaging  
member 114. Since the bone-engaging member 114 is not polyaxial, the bone-engaging  
member 114 may or may not include a head formed thereon, and thus the pin member  
120 can extend through a head of the bone-engaging member 114, or it can extend

- 10 -

directly through a portion of the shaft 114b of the bone-engaging member 114. A person skilled in the art will appreciate that a variety of other techniques can be used to provide a receiver member 112 that is pivotally coupled to a bone-engaging member 114.

In use, several devices 100 can be implanted in adjacent vertebrae to maintain the vertebrae in a fixed position relative to one another, yet to allow pivotal movement of each vertebrae in that fixed position, e.g., to allow the patient's spine to flex. As shown in FIGS. 4A-4B, two devices 100, 100' are implanted in adjacent vertebra 150, 152. In FIG. 4A, the vertebrae 150, 152 are maintained in a first, fixed position by locking spinal rod 118 to the receiver member 112, 112' of each device 100, 100'. In FIG. 4B, the vertebrae 150, 152 have pivoted within that fixed position due to flexion of the patient's spine, and thus each bone-engaging member 114, 114' has pivoted along axis *A* relative to the receiver member 112, 112' coupled thereto, and relative to the spinal fixation element 18 mated to each receiver member 112, 112'. Such a configuration can be useful in applications where movement along a single plane, such as the patient's coronal plane, is desired while preventing axial rotation of the vertebrae 150, 152.

The spinal anchoring devices in accordance with various embodiments of the present invention can be formed from a variety of materials, including, for example, stainless steel, titanium, cobalt-chrome alloys, etc. In other embodiments, the spinal anchoring devices can include features to facilitate movement of the bone-engaging member relative to the receiver member. For example, referring to the device 10 shown in FIGS. 1A-1D, portions of the bone-engaging member 14 and the receiver member 12 that come into contact with one another, e.g., the spherical head 14a of the bone-engaging member 14 and/or the cavity 20 in the receiver member 12, can include a surface coating thereon or therein. The surface coating can be formed from a material that allows free movement of the components 12, 14, and that is preferably wear-resistant. By way of non-limiting example, suitable materials include titanium oxide, nitride, and a cobalt-chrome alloy.

One of ordinary skill in the art will appreciate further features and advantages of the invention based on the above-described embodiments. Accordingly, the invention is not to be limited by what has been particularly shown and described, except as indicated

- 11 -

by the appended claims. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

What is claimed is:

- 12 -

## CLAIMS:

1. A spinal anchoring device, comprising:  
5 a bone-engaging member adapted to engage bone;  
a receiver member movably coupled to the bone-engaging member, the receiver member being adapted to seat a spinal fixation element; and  
a fastening element adapted to mate to the receiver member to lock a fixation element in a fixed position relative to the receiver member while allowing the receiver  
10 member to move freely relative to the bone-engaging member.
2. The spinal anchoring device of claim 1, wherein the bone-engaging member is pivotally coupled to the receiver member such that the receiver member pivots along an axis relative to the bone-engaging member.  
15
3. The spinal anchoring device of claim 2, further comprising a pin member extending through a distal end of the receiver member and through a proximal end of the bone-engaging member for pivotally mating the receiver member and the bone-engaging member.  
20
4. The spinal anchoring device of claim 2, further comprising a surface coating on portions of the bone-engaging member and the receiver member that come into contact with one another.
- 25 5. The spinal anchoring device of claim 4, wherein the surface coating is formed from a material selected from the group consisting of titanium oxide, nitride, and a cobalt-chrome alloy.
6. The spinal anchoring device of claim 1, wherein the bone-engaging member is  
30 polyaxially coupled to the receiver member.

- 13 -

5        7.        The spinal anchoring device of claim 6, wherein the bone-engaging member includes a spherical head formed on a proximal end thereof, and wherein the receiver member includes a cavity formed in a distal portion thereof and adapted to polyaxially seat the spherical head of the bone-engaging member.

10       8.        The spinal anchoring device of claim 7, wherein the receiver member includes a recess formed in a proximal portion thereof and adapted to seat a spinal fixation element, the recess being spaced apart and separate from the cavity in the distal portion of the receiver member.

15       9.        The spinal anchoring device of claim 1, wherein the receiver member includes a distal portion movably mated to the bone-engaging member, and a proximal portion having a recess formed therein for seating a spinal fixation element.

20       10.       The spinal anchoring device of claim 9, wherein the fastening element is adapted to mate to the proximal portion of the receiver member to engage and lock a spinal fixation element within the recess in the receiver member.

25       11.       The spinal anchoring device of claim 10, wherein the fastening element comprises a set screw adapted to mate with corresponding threads formed within at least a portion of the recess in the receiver member.

30       12.       A spinal anchoring system, comprising:  
             a spinal fixation element;  
             a spinal anchoring device having a bone-engaging member and a receiver member freely movably coupled to the bone-engaging member and configured to receive the spinal fixation element; and  
             a fastening element receivable within the receiver member of the spinal anchoring device and being configured to lock the spinal fixation element to the spinal anchoring device.

- 14 -

13. The spinal anchoring system of claim 12, wherein the receiver member is pivotally coupled to the bone-engaging member.
- 5 14. The spinal anchoring system of claim 13, further comprising a bearing element formed between the receiver member and the bone-engaging member for allowing pivotal movement of the receiver member relative to the bone-engaging member.
- 10 15. The spinal anchoring system of claim 15, wherein the bearing element includes a surface coating adapted to facilitate movement of the receiver member relative thereto.
- 15 16. The spinal anchoring system of claim 15, wherein the surface coating is formed from a material selected from the group consisting of titanium oxide, nitride, and a cobalt-chrome alloy.
17. The spinal anchoring system of claim 12, wherein the bone-engaging member is polyaxially coupled to the receiver member.
- 20 18. The spinal anchoring system of claim 17, wherein the bone-engaging member includes a spherical head formed thereon, and wherein the receiver member includes a cavity formed therein for receiving the spherical head.
- 25 19. The spinal anchoring system of claim 12, wherein the bone-engaging member is coupled to a distal end of the receiver member, and the fastening element is matable to a proximal end of the receiver member.
- 30 20. The spinal anchoring system of claim 19, wherein the proximal end of the receiver member includes a substantially U-shaped recess formed therein for seating the spinal fixation element.



- 15 -

21. The spinal anchoring system of claim 20, wherein the fastening element includes threads formed thereon for mating with corresponding threads formed within at least a portion of the U-shaped recess formed in the receiver member.
- 5
22. The spinal anchoring system of claim 12, wherein the spinal fixation element is selected from the group consisting of a cable, a tether, a rigid spinal rod, and a flexible spinal rod.
- 10
23. The spinal anchoring system of claim 12, wherein the spinal fixation element is formed from a material selected from the group consisting of stainless steel, titanium, non-absorbable polymers, absorbable polymers, and combinations thereof.
- 15
24. A method for correcting spinal deformities, comprising:  
implanting a plurality of anchoring devices into adjacent vertebrae in a spinal column, each anchoring device including a bone-engaging member that is fixedly attached to the vertebra and a receiver member that is freely movable relative to the bone-engaging member and the vertebra;  
coupling a spinal fixation element to the receiver member on each anchoring  
20 device such that the fixation element extends between each of the adjacent vertebrae;  
locking the spinal fixation element to the receiver member on each anchoring device to maintain the adjacent vertebrae at a fixed distance relative to one another while allowing free movement of each vertebrae in the fixed position.
- 25
25. The method of claim 24, wherein the receiver member of at least one of the anchoring devices is movable along a single plane relative to the bone-engaging member.
- 30
26. The method of claim 24, wherein the bone-engaging member of at least one of the anchoring devices is polyaxially coupled to the receiver member.

- 16 -

27. The method of claim 24, wherein the bone-engaging member includes a spherical head formed on a proximal end thereof, and wherein the receiver member includes a cavity formed in a distal portion thereof and adapted to polyaxially seat the spherical head of the bone-engaging member.

28. The method of claim 24, wherein the receiver member includes a recess formed in a proximal portion thereof and adapted to seat the spinal fixation element.

29. The method of claim 24, wherein the receiver member includes a distal portion movably mated to the bone-engaging member, and a proximal portion having a recess formed therein for seating the spinal fixation element.

30. The method of claim 24, wherein the step of locking comprises applying a fastening element to each receiver member to engage and lock the spinal fixation element therein.

31. The method of claim 24, wherein the spinal fixation element is selected from the group consisting of a cable, a tether, a rigid spinal rod, and a flexible spinal rod.

32. A spinal anchoring device, comprising:  
a bone screw having a head and a shank;  
a receiver member having a distal seat for receiving at least a portion of the head of the bone screw and a proximal seat for receiving a spinal fixation rod; and  
a fastening element adapted to mate to the receiver member to seat a spinal fixation rod in the proximal seat, the proximal seat being spaced a distance apart from the distal seat sufficient to allow polyaxial motion of the bone screw relative to the receiver member upon seating of the spinal fixation rod in the proximal seat by the fastening element.

30

- 17 -


33. The spinal anchoring device of claim 32, wherein the receiver member includes a recess extending from a proximal opening in the receiver member, a distal portion of the recess defining the proximal seat for the spinal fixation rod.

5

34. The spinal anchoring device of claim 33, wherein the recess is generally U-shaped in configuration and is defined by two opposed legs.


10

35. The spinal anchoring device of claim 34, wherein the fastening element is a set screw having external threads for engaging internal threads provided on the legs.




2 / 5

**Fig. 1D**




3 / 5

*Fig. 1E*




4 / 5

*Fig. 2*

5 / 5

**Fig. 3A**



**Fig. 3B**

